

BUNK MODELS
GALVANIZED AND ALUMINUM FRAMES



Non-braking models shown with optional tongue jacks.



bunk covers for all bunk trailers.



Single and tandem axle v-bunk models



- ☆ Minimal adjustment
- ☆ Trailering simplicity
- ☆ Traditional support and stability
- ☆ Fully carpeted bunks
- ☆ Sturdy galvanized steel or aluminum I-beam frames
- ☆ Available with brakes
- ☆ Torsion axles 96" wide and over
- ☆ Single axle sizes to fit 15' to 21' boats
- ☆ Single axle capacities to 3,600 lb.
- ☆ Tandem axle sizes to fit 20' to 28' boats
- ☆ Tandem axle capacities to 8,000 lb.
- ☆ Powered by Load Rite®

your safety and trailer brakes

Brake laws vary by state and require dealers to sell trailers that comply with the brake laws of the state where the trailer will be registered. [This is a very important safety issue.](#) For full information contact the appropriate state Motor Vehicle Department. As always, for your safety, the safety of those in your party, and the safety of those around you, 5 STARR recommends brakes on all axles where available.



Models and specifications available at www.5starrtrailers.com



- ☆ Some models shown with optional equipment.
- ☆ Specifications may change without notice.
- ☆ Not responsible for printing errors.



MAIN PLANT
265 Lincoln Highway
Fairless Hills, PA 19030
800-562-3783 800-LOADRTE
Fax 800-577-8832

Why 5 STARR?

- ☆ Over 10 years of proven quality
- ☆ Multiple adjustment points allowing the best possible fit
- ☆ High quality materials provide years of service and minimal maintenance in a marine environment
- ☆ Fast product delivery
- ☆ Factory-backed warranty
- ☆ Powered by Load Rite®

Quality
Value
Selection
Reliability



2008 PRODUCT SHOWCASE



Quality
Value
Selection
Reliability

SOUTHEAST
271 Flanders Filters Road
Washington, NC 27889
800-288-6884
Fax 252-975-2185

ROLLER MODELS

GALVANIZED AND ALUMINUM FRAMES

Single axle roller models

- ☆ Smooth loading and launching
- ☆ Sturdy galvanized steel frames
- ☆ Available with brakes
- ☆ Torsion axles 96" wide and over
- ☆ Sizes to fit 16' to 21' boats
- ☆ Up to 3,600 lb. capacity
- ☆ Powered by Load Rite®



Non-braking models shown with optional tongue jacks.



Aluminum roller models

- ☆ Easy roller launching and loading
- ☆ Stylish, lightweight aluminum frames
- ☆ Single and tandem models
- ☆ Torsion axles
- ☆ Sizes for boats from 17' to 26'
- ☆ Up to 6,000 lb. capacity
- ☆ Optional stainless steel hardware
- ☆ Powered by Load Rite®

Tandem axle roller models

- ☆ Classic styling
- ☆ Smooth loading and launching
- ☆ Sturdy galvanized steel frames
- ☆ Torsion axles
- ☆ Sizes to fit boats 20' to 28'
- ☆ Up to 7,400 lb. capacity
- ☆ Powered by Load Rite®



TPR Rollers

Thermal Plasticized Rubber

Featured on every 5 STARR roller trailer, TPR combines all the best qualities of rubber, polyurethane, and plastic.

- ☆ Soft, gentle, and long lasting
- ☆ Resilient at all temperatures
- ☆ Non-marking
- ☆ Smooth, Delrin® roller bushing (patent pending)
- ☆ Easy launch and load



Selecting a 5 STARR

LENGTH - Measure along the center line. Include bow pulpit, but exclude swim platform.

WEIGHT - Calculate the total weight of your boat as trailered. Include boat, engine, fuel, and water. Include an allowance for miscellaneous gear and supplies you intend to carry.

ROLLER OR BUNK - The type of boat you select has a great deal to do with choosing a trailer. Be sure to check with the boat manufacturer for any special requirements or restrictions. Also consider the way in which the trailer will be used. Primarily winter storage versus launch and load at each use of the boat?

SINGLE OR TANDEM AXLE - Single axle trailers provide simplicity and maneuverability; however, tandems tend to track better and offer added security.

Your safety and trailer brakes

Brake laws vary by state and require dealers to sell trailers that comply with the brake laws of the state where the trailer will be registered. This is a very important safety issue. For full information contact the appropriate state Motor Vehicle Department. As always, for your safety, the safety of those in your party, and the safety of those around you, **5 STARR recommends brakes on all axles where available.**

Model	Hull Length	Capacity	Axles	Brakes	Rollers	Tires	Between Fenders	Overall Width	Overall Length	Approx. Weight
5S-AR183100102T	17' - 18'	3,100	1	0	20	ST215/14C	81.25"	101"	19' 10"	590
5S-AR183100102TB1	17' - 18'	3,100	1	1	20	ST215/14C	81.25"	101"	19' 10"	590
5S-AR203100102T	19' - 20'	3,100	1	0	20	ST215/14C	81.25"	101"	21' 9"	600
5S-AR203100102TB1	19' - 20'	3,100	1	1	20	ST215/14C	81.25"	101"	21' 9"	600
5S-AR20T4200102TB1	19' - 20'	4,200	2	1, 2	28	ST205/14C	81.25"	101"	21' 9"	1,120
5S-AR22T5200102TB1	21' - 22'	5,200	2	1, 2	40	ST215/14C	81.25"	101"	23' 9"	1,140
5S-AR24T6000102TB1	23' - 24'	6,000	2	1, 2	48	ST215/14C	81.25"	101"	26' 3"	1,175
5S-AR26T6000102TB1	25' - 26'	6,000	2	1, 2	48	ST215/14C	81.25"	101"	29'	1,240

Model	Hull Length	Capacity	Axles	Brakes	Bunks	Tires	Between Fenders	Overall Width	Overall Length	Approx. Weight
5S-AC183100102T	17' - 18'	3,100	1	0	2	ST215/14C	82"	101"	20' 8"	590
5S-AC183100102TB1	17' - 18'	3,100	1	1	2	ST215/14C	82"	101"	20' 8"	590
5S-AC203100102T	18' - 20'	3,100	1	0	2	ST215/14C	82"	101"	22' 4"	600
5S-AC203100102TB1	18' - 20'	3,100	1	1	2	ST215/14C	82"	101"	22' 4"	600
5S-AC20T4200102TB1	18' - 20'	4,200	2	1, 2	2	ST205/14C	82.5"	101"	22' 4"	1,120
5S-AC22T4200102TB1	20' - 22'	4,200	2	1, 2	2	ST205/14C	82.5"	101"	24' 4"	1,130
5S-AC22T5200102TB1	20' - 22'	5,200	2	1, 2	2	ST205/14C	82.5"	101"	24' 4"	1,140
5S-AC22T6000102TB1	20' - 22'	6,000	2	1, 2	2	ST215/14C	82.5"	101"	24' 4"	1,175
5S-AC24T6000102TB1	22' - 24'	6,000	2	1, 2	2	ST215/14C	82.5"	101"	27' 1"	1,175
5S-AC24T7300102TB1	22' - 24'	7,300	2	1, 2	2	ST225/15D	82.5"	101"	27' 1"	1,460
5S-AC26T6000102TB1	24' - 26'	6,000	2	1, 2	2	ST215/14C	82.5"	101"	29' 0"	1,240
5S-AC26T7300102TB1	24' - 26'	7,300	2	1, 2	2	ST225/15D	82.5"	101"	29' 0"	1,460
5S-AC26T8000102TB2	24' - 26'	8,000	2	2	2	ST225/15D	82.5"	101"	29' 0"	1,540
5S-AC28T7300102TB1	26' - 28'	7,300	2	1, 2	2	ST225/15D	82.5"	101"	31' 10"	1,540
5S-AC28T8000102TB2	26' - 28'	8,000	2	2	2	ST225/15D	82.5"	101"	31' 10"	1,540

Model	Hull Length	Capacity	Brakes	Bunks	Tire Size	Between Fenders	Overall Width	Overall Length	Trailer Weight
5S-16150076V	14' - 16'	1,500	0	2	4.80x12C	62"	76"	18' 3"	290
5S-171750V	15' - 17'	1,700	0	2	ST175/13C	73.5"	90"	20' 1"	490
5S-172200V	15' - 17'	2,200	0	2	ST175/13C	73.5"	90"	20' 1"	500
5S-172450V	15' - 17'	2,450	0	2	ST205/14C	73.5"	90"	20' 1"	510
5S-192450VT	18' - 19'	2,450	0	2	ST205/14C	73.5"	90"	21'	549
5S-192660VT	18' - 19'	2,660	0	2	ST205/14C	73.5"	90"	21'	560
5S-192660VTB	18' - 19'	2,660	1	2	ST205/14C	73.5"	90"	21'	560
5S-192800VT	18' - 19'	2,800	0	2	ST205/14C	73.5"	90"	21'	590
5S-192800VTB	18' - 19'	2,800	1	2	ST205/14C	73.5"	90"	21'	590
5S-19266096VT	18' - 19'	2,660	0	2	ST205/14C	79"	96"	21'	540
5S-193000VT	18' - 19'	3,000	0	2	ST215/14C	79"	96"	21'	540
5S-193100VT	18' - 19'	3,100	0	2	ST215/14C	79"	96"	21'	540
5S-193100VTB	18' - 19'	3,100	1	2	ST215/14C	79"	96"	21'	540
5S-213600VT	20' - 21'	3,600	0	2	ST225/15D	79"	96"	23' 4"	680
5S-213600VTB	20' - 21'	3,600	1	2	ST225/15D	79"	96"	23' 4"	680

Specifications subject to change without notice. All dimensions approximate

- ☆ Some models shown with optional equipment.
- ☆ Specifications may change without notice.
- ☆ Not responsible for printing errors.

SPECIFICATIONS

Model	Hull Length	Capacity	Brakes	Rollers	Tire Size	Between Fenders	Overall Width	Overall Length	Trailer Weight
5S-21T3700TG1	19' - 21'	3,700	1, 2	24	ST205/14C	77" / 82.5"	96"	23' 3"	1,200
5S-22T4200TG1	20' - 22'	4,200	1, 2	28	ST205/14C	77" / 82.5"	96"	24' 3"	1,200
5S-22T4700TG1	20' - 22'	4,700	1, 2	32	ST205/14C	77" / 82.5"	96"	24' 3"	1,250
5S-23T5000TG1	22' - 23'	5,000	1, 2	32	ST205/14C	77" / 82.5"	96"	25' 4"	1,600
5S-23T5400TG1	22' - 23'	5,400	1, 2	40	ST215/14C	77" / 82.5"	96"	25' 4"	1,600
5S-24T6400TG1	23' - 24'	6,400	1, 2	64	ST225/15D	77"	96"	26' 2"	1,940
5S-25T5800TG1	24' - 25'	5,800	1, 2	48	ST215/14C	77"	96"	27' 2"	1,400
5S-26T6400TG1	25' - 26'	6,400	1, 2	64	ST225/15D	77"	96"	28' 1"	1,940
5S-26T7400TG1	25' - 26'	7,400	1, 2	64	ST225/15D	77"	96"	28' 1"	2,000
5S-28T7400TG1	26' - 28'	7,400	1, 2	64	ST225/15D	77"	96"	29' 8"	2,000

Model	Hull Length	Capacity	Brakes	Bunks	Tire Size	Between Fenders	Overall Width	Overall Length	Trailer Weight
5S-21T3700TV1	19' - 21'	3,700	1, 2	4	ST205/14C	77" / 82.5"	96" / 102"	23' 4"	1,200
5S-22T4200TV1	19' - 21'	4,200	1, 2	4	ST205/14C	77" / 82.5"	96" / 102"	23' 4"	1,200
5S-22T4700TV1	19' - 21'	4,700	1, 2	4	ST205/14C	77" / 82.5"	96" / 102"	23' 4"	1,250
5S-23T5000TV1	21' - 23'	5,000	1, 2	4	ST205/14C	77" / 82.5"	96" / 102"	25' 5"	1,600
5S-23T5400TV2	21' - 23'	5,400	1, 2	4	ST215/14C	77" / 82.5"	96" / 102"	25' 5"	1,600
5S-24T6400TV1	21' - 23'	6,400	1, 2	4	ST225/15D	77"	96"	25' 5"	1,626
5S-25T5800TV1	23' - 25'	5,800	1, 2	4	ST215/14C	77" / 82.5"	96" / 102"	27' 2"	1,600
5S-26T7400TV1	24' - 26'	7,400	1, 2	4	ST225/15D	77"	96"	28' 3"	2,000
5S-26T6400TV1	24' - 26'	6,400	1, 2	4	ST225/15D	77"	96"	28' 3"	1,626
5S-28T7400TV1	26' - 28'	7,400	1, 2	4	ST225/15D	77"	96"	30' 3"	2,000

Model	Hull Length	Capacity	Brakes	Rollers	Tire Size	Between Fenders	Overall Width	Overall Length	Trailer Weight
5S-16125076R	15' - 16'	1,250	0	12	4.80x12C	62"	76"	17' 4"	285
5S-16150076R	15' - 16'	1,500	0	12	4.80-12C	62"	76"	17' 4"	290
5S-171750R	16' - 17'	1,700	0	16	ST175/13C	73.5"	90"	17' 11"	490
5S-172200R	16' - 17'	2,200	0	16	ST175/13C	73.5"	90"	17' 11"	500
5S-172450R	16' - 17'	2,450	0	16	ST205/14C	73.5"	90"	17' 11"	500
5S-17245090RB	16' - 17'	2,450	1	16	ST205/14C	73.5"	90"	17' 11"	510
5S-192450RT	17' - 19'	2,450	0	16	ST205/14C	73.5"	90"	19' 2"	530
5S-192660RT	17' - 19'	2,660	0	16	ST205/14C	73.5"	90"	19' 2"	540
5S-192660RTB	17' - 19'	2,660	1	16	ST205/14C	73.5"	90"	19' 2"	560
5S-192800RT	17' - 19'	2,800	0	20	ST205/14C	73.5"	90"	19' 2"	580
5S-192800RTB	17' - 19'	2,800	1	20	ST205/14C	73.5"	90"	19' 2"	580
5S-193000RT	17' - 19'	3,000	0	20	ST205/14C	79"	96"	19' 2"	590
5S-193100RT	17' - 19'	3,100	0	20	ST215/14C	79"	96"	19' 2"	580
5S-193100RTB	17' - 19'	3,100	1	20	ST215/14C	79"	96"	19' 2"	600
5S-213600RTB		3,600	1	24	ST225/15D	79"	96"	23' 4"	680

Specifications subject to change without notice. All dimensions approximate

POPULAR OPTIONS

Consult your dealer about upgrading your trailer with these popular options.

- ☆ Spare tire and carrier
- ☆ Tongue jack
- ☆ Aluminum wheels
- ☆ L.E.D. lighting
- ☆ Disc brakes
- ☆ Side guides
- ☆ Quick-Slide® bunk covers
- ☆ Stainless steel brakelines



need help selecting?

Selecting a trailer can make all the difference in a satisfying boating experience. With so many types and models, proper trailer selection can be confusing. Rely on the knowledge of your dealership. Their experience will guide you to a model that suits your boat as well as your boating style. As always, you can contact 5 STARR at 800-562-3783, or visit us on the web at www.5starrtrailers.com.

L.E.D. LIGHTS
Optional L.E.D. light upgrades available on most models. Consult your dealer for availability.

GOT MAGS?
Dress up your 5 STARR with optional stylish aluminum wheels.

SURE-LUBE®
Add grease to your hubs anytime, anyplace, easily.